

StuvEx United Kingdom & Ireland

Tel.: +44 1932 571303 Fax: +44 1932 570548

Abbey Studio, Church Walk, Chertsey, Surrey KT16 8RE

info@stuvex.co.uk www.stuvexuk.com

EXPLOSION SAFETY AND PROCESS FIRE PROTECTION

SAFE-GROUND TES01 (IP) (Ex) - Monitor for earthing control



The earth connection of a fixed installation can be checked on a regular basis. For mobile installations, such as a truck, a barrel or an FIBC, the earth connection can easily be forgotten. In addition, simple clamps are often used and this connection might be neglected and/or be working inefficiently. Continuous monitoring of the earth connection is essential The StuvEx earth monitoring system permanently monitors the earth connection and uses object

- Resistive system for general use with barrels, metal objects, etc.
- Capacitive system is available in order to recognise tanker trucks.

recognition, thereby eliminating the possibility of incorrect use:

• Conductive system is available for use with FIBC (Big Bag) type C





PAGG - CO2 industrial fire fighting

Human surveillance over processing is no longer foolproof in today's digitally-controlled technology. CO2 fire fighting offers a straightforward system to rapidly control incipient fires on several industrial installations. A range of safety devices is available for the instant detection of flames and their extinction, thereby preventing their propagation. The device guaranties that the fire is contained and that the shutdown of the production is limited. The system is optimised for industrial process fires (i.e. in spray booths, ovens, dedusting filters, switching cabinets, etc.)

- · Very fast response times;
- Built-in alarm when CO2 levels drop too much;
- Various programmable outflow functions (flooding, intermittent, delayed).

FLASH – Dust explosion suppression system

The FLASH explosion suppression system is a flexible, modular system consisting of:

- Explosion detectors triggered by static, dynamic or optical monitoring (UV, IR, UV/IR, ...) or a combination.
- A multifunctional modular control unit;
- Ultra-fast powder extinguishers in different sizes with various types of connection flanges depending on the application. Standard features available for all configurations are: No pressure vessels! Driven by gas generators with a very long life (up to ten years!!). A revolutionary communication protocol between the various components makes system faults due to EMC radiation on the wiring nearly impossible!



Venting or Isolation

VENTING of explosion overpressure by:

- Venting panel STUVENT
- Flameless venting: FLAMECATCHER or DQS








FlameCatcher

StuVent

ISOLATION of explosion propagation:

- Passive rapid valve **VENTEX**
- Passive rapid valve **NOVEx**
- active fast slide gate valves FSGV
- Chemical barriers FLASH







NOVEx

FSGV

Ventex

Total protection solutions from initial conception to commissioning and service, (Full turnkey projects)